

WWW.COLLAMAT.CH



Productline overview

Labelling Your Product - Our Competence.

Swiss Modular Labellers 

Collamat[®]

”

Quality and precision
- the Collamat® tradition followed
through the decades and we care
every day by doing our best

Professional labelling solutions. Quality and reliability.

Collamat® is focused on providing labelling solutions with simple constructions, easy handling and professional design.

Quality means reliability.

Collamat® has been producing labelling machines since 1958. We have sold over 80,000 machines and solutions in over 40 different countries. This was made possible by putting quality first and because total reliability is what our customers want from our machines and solutions.

Close to the customer, close to the market.

We want to be close to our customers and the market. Close to the customer to ensure we provide the quality and service they expect. Close to the market to keep up to date with the new requirements and expectations.

A cohesive value chain means reliable delivery.

By bringing R&D, production, service and sales under one roof in Switzerland, we have control over the entire value chain. What that means for our customers is that we can guarantee quality, delivery on time and the level of service expected.

Sales throughout the world.

We have successfully been represented on the world market since 1960. This has been possible because we listen, and use the inspiration and know-how a worldwide network can give to develop our products and organisation.

Collamat® S 50



Collamat®

FEATURES

- **Space-saving and Flexibility** – The complete electronics is integrated in the body of the traction unit. The compact size of the labeler makes its integration into production lines very easy.
- **Modularity** - The modular design allows integration (also at a later point) of external devices like printers, scanners, black mark readers, etc.
- **Reliability** – With 80 % more labels on a 400 mm label roll compared to a 300 mm roll and the advanced “end of label” warning system, Collamat® S 50 needs less operator attention. Thanks to the very light and stable housing of cast aluminum, optimized by finite element method, the unwinder of Collamat® S 50 can cope with roll diameters of 400 mm with label width up to 250 mm and weight up to 35 Kg.
- **Easy operation** – Place the roll, thread the web and start labelling! No additional adjustments necessary!
- **Self-teaching label scanner** – The optical label scanner has a self-teaching function and continuously readjusts its settings to the environmental light, label transparency variations, etc. With the height and position adjustment of the scanner, thick labels like Piggyback, Pocket labels, etc., can also be used.
- **Secure production** – Saving up to 99 different labelling programs. Password level protection.

TECHNICAL DATA

| | |
|--------------------------|---|
| Operational speed | 3 – 50 m/min (9.8 – 164 ft / min) |
| Operational width | 100 mm (4") - 250 mm (9 7/8") |
| Labelling accuracy | ± 0.5 mm (0.02") |
| Min. label length | 10 mm (0.4") |
| Max. label reel diameter | 410 mm (16") or 350 mm (13 3/4") |
| Connectivity | Outputs: Signals for printer and error Inputs: Incremental encoder, goods scanner, end of label detection, etc |
| Settings | By control panel |
| Drive | 2-phase stepper motor |
| Control | Microprocessor |
| Voltage | 115 / 230 V; 60 / 50 Hz; 138 VA |
| Feed button | For manual label dispensing, i.e. threading the label web. |
| Applicators | Spring loaded flap or fixed applicator |
| Version | Right or left |
| Options | Side labeling kit, extended peel plate, pressure brushes, label end detection, etc. |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® S 100



Collamat®

FEATURES


- **Space-saving and Flexibility** – The complete electronics is integrated in the body of the traction unit. The compact size of the labeler makes its integration into production lines very easy.
- **Modularity** - The modular design allows integration (also at a later point) of external devices like printers, scanners, black mark readers, etc.
- **Reliability** – With 80 % more labels on a 400 mm label roll compared to a 300 mm roll and the advanced “end of label” warning system, Collamat® S 100 needs less operator attention. Thanks to the very light and stable housing of cast aluminum, optimized by finite element method, the unwinder of Collamat® S 100 can cope with roll diameters of 400 mm with label width up to 250 mm and weight up to 35 Kg.
- **Easy operation** – Place the roll, thread the web and start labelling! No additional adjustments necessary!
- **Self-teaching label scanner** – The optical label scanner has a self-teaching function and continuously readjusts its settings to the environmental light, label transparency variations, etc. With the height and position adjustment of the scanner, thick labels like Piggyback, Pocket labels, etc., can also be used.
- **Secure production** – Saving up to 99 different labelling programs. Password level protection.

TECHNICAL DATA

| | |
|--------------------------|---|
| Operational speed | 3 – 100 m/min (9.8 – 328 ft / min) |
| Operational width | 100 mm (4") - 250 mm (9 7/8") |
| Labelling accuracy | ± 0.5 mm (0.02") |
| Min. label length | 10 mm (0.4") |
| Max. label reel diameter | 410 mm (16") or 350 mm (13 ¾") |
| Connectivity | Outputs: Signals for printer and error Inputs: Incremental encoder, goods scanner, end of label detection, etc |
| Settings | By control panel |
| Drive | 2-phase stepper motor |
| Control | Microprocessor |
| Voltage | 115 / 230 V; 60 / 50 Hz; 138 VA |
| Feed button | For manual label dispensing, i.e. threading the label web. |
| Applicators | Spring loaded flap or fixed applicator |
| Version | Right or left |
| Options | Side labeling kit, extended peel plate, pressure brushes, label end detection, etc. |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® S 300



FEATURES

Space saving and flexibility – The complete electronics and the motorised re-winder are integrated in the body of the traction unit. The compact size of the labeller makes the integration in a production line very easy. The modular design allows integration (also at a later point) of external devices like printers, scanners, black mark readers, etc

High Quality – The wear is reduced to a minimum. The stepper motor drive and the motorised re-winder need little maintenance. All bodies are made of die casted Aluminium for maximal stability and to avoid electromagnetic disturbances

Dual core processor – The fast processor makes the exact calculation of all parameters, for each label, in real time

Adjustable ramps – All ramp parameters of the motor are adjustable in order to adapt the acceleration to the different label qualities. The programmable ramps and the special label applicator reduce the risk of liner break to an absolute minimum

Self-teach label scanner – The optical label scanner has a self-teaching function and adapts itself continuously to the environmental light, label transparency variations, etc


Swiss Quality – Collamat® S 300 ensures constant labelling quality for years

TECHNICAL DATA

| | |
|--------------------|---|
| Operational speed | 0 – 300 m/min (0 – 1000 ft/min) |
| Productivity | 60'000 labels/hour (or 120'000 labels/hour in Tandem mode) depending on the label length |
| Label width | 25 – 95 mm (1 - 3 ¾") |
| Label length | 25 – 100 mm (1 - 4") |
| Labelling accuracy | +/- 1.5 mm (1/16") at 150 m/min (500 ft/min) depending on the label specification |
| Label reel | Max. outer diameter: 350 mm (13 ¾") or 400 mm (15 ¾") Core diameter: 75 mm (3") |
| Connectivity | Outputs: Signals for printers, PLC (run / warning / error), Lamps (red / orange / green), Non-Stop / Tandem mode (with 2 labellers), etc. Inputs: Product scanner (black mark reader), High definition encoder, Start / stop (enable / disable), Label low detection, Ethernet |
| Settings | Adjustable via keyboard and display (Control panel) |
| Operation modes | Mono / Tandem (with 2 labellers) / Non Stop (with 2 labellers) |
| Drive | 2-phases, micro steps, stepper motor |
| Control | Dual core microprocessor |
| Power requirements | 115 / 230 V; 60 / 50 Hz; 460 VA each labeller 6 bar air pressure |
| Applicator | High Speed applicator with spring loaded pinch roller, including optical label scanner with self-teaching function |
| Version | Right or Left |
| Options | Mechanical label scanner for transparent labels Splicer / external un-winder - Suction unit for waste liner |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® C 2600



Collamat®

FEATURES

Compact design – Minimal space required. Ideal to fit into existing production lines.

Flexibility – For top-, bottom- and side application.

Easy handling – Fast set-up and short change-over times.

Profitability – Low cost makes small series and promotional labelling attractive.


Simple operation – 3 potentiometers.

TECHNICAL DATA

| | |
|-------------------------|---|
| Operational speed | 3-15 m/min (9.8-49 ft/min.) |
| Operational width | 95 mm - Max 3 ¾" |
| Labelling accuracy | ± 1 mm (1/32") |
| Min. label length | 10 mm (3/8") |
| Settings | By potentiometers |
| Module rail | 500 mm (19 5/8") |
| Max label reel diameter | 250 mm (9 7/8") |
| Rewinder | Integrated in the traction unit |
| Applicator | Spring loaded pinch roller and fixed applicator |
| Version | Left or right |
| Options | Side labelling kit |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® C 4300



Collamat®

FEATURES

Flexibility – Wide application range thanks to the availability of various applicators for specific products; a spring loaded flap applicator for pass-through labelling of uneven products; flap applicator with magnet for pass-through labelling in small cavities or of light products; blow-on for labelling without contact with the product; tamp-on for stand-still labelling or labelling in cavities.

Collamat® design – Electronics, drive unit, backing paper re-winder and control panel integrated in one, space-saving unit.

Modularity – The Collamat® well-known module rail design facilitates the installation of printers, scanners or other devices. Easy adaptation to new applications. Fast change-over times.

Easy operation – Settings can easily be changed by four potentiometers.

Fast set up – Set the label scanner, pre-dispensing, label position and application speed – and you are ready to work.

TECHNICAL DATA

| | |
|--------------------------|---|
| Operational speed | 1 – 25 m/min (3.3 – 82 ft / min) |
| Operational width | 95 mm (3 ¾") or 160 mm (6 ¼") |
| Labelling accuracy | ± 1 mm (1/32") |
| Min. label length | 10 mm (3/8") |
| Max. label reel diameter | 250 mm (9 7/8") or 350 mm (13 ¾") |
| Connectivity | Outputs: Signals for printer and error Inputs: Goods scanner and end of label detection |
| Settings | By potentiometers |
| Drive | 2-phase stepper motor |
| Control | Microprocessor |
| Voltage | 115 / 230 V; 60 / 50 Hz; 138 VA Feed button for manual label dispensing, i.e. threading the label web |
| Applicators | Spring loaded flap, flap with magnet, blow-on, tamp-on |
| Version | Right or left |
| Options | Side labelling kit, extended peel plate, pressure brushes, label end detection, digital control box, etc. |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® C 6600



Collamat®

FEATURES

Flexibility – Wide application range thanks to the availability of various applicators for specific products; a spring loaded flap applicator for pass-through labeling of uneven products; flap applicator with magnet for pass-through labeling in small cavities or of light products; blow-on for labeling without contact with the product; tamp-on for stand-still labeling or labeling in cavities.

Collamat® design – Electronics, drive unit, backing paper re-winder and control panel integrated in one, space-saving unit.

Modularity – The ingenious Collamat® module rail design facilitates the installation of printers, scanners or other devices. Flexibility and easy adaptation to new applications. Fast change-over times.

Easy operation – Settings can easily be changed by 4 potentiometers. Features label delay function – great for over-the-edge application without stopping the product flow.

Secure production – Saving the application parameters' settings through the Data-hold button.


Fast set up – Set the label scanner, pre-dispensing, label position and application speed – and you are ready to work.

TECHNICAL DATA

| | |
|-------------------------|--|
| Operational speed | 3 – 30 m/min (9,8-98 ft/min) |
| Max. label width | 95 mm (3 3/4") or 160 mm (6 1/4") |
| Labelling accuracy | ± 1 mm (1/32") |
| Min. label length | 10 mm (3/8") |
| Max label reel diameter | 250 mm (9 7/8") or 350 mm (13 3/4") |
| Connectivity | Outputs: Signals for printer and error Inputs: Incremental encoder, goods scanner, end of label detection |
| Settings | By potentiometers |
| Drive | 2-phase stepper motor |
| Control | Microprocessor |
| Voltage | 115 / 230 V; 60 / 50 Hz; 138 VA Data hold switch for saving the labeling parameters |
| Applicators | Spring loaded flap, flap with magnet, blow-on, tamp-on |
| Version | Right or left |
| Options | Side labeling kit, extended peel plate, pressure brushes, label end detection, digital control box, etc. |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® C 7300



Collamat®

FEATURES

Flexibility – Wide application range thanks to the availability of various applicators for specific products; a spring loaded flap applicator for pass-through labelling of uneven products; a flap applicator with magnet for pass-through labelling in small cavities or of light products; a blow-on for labelling without contact with the product; a tampon for stand-still labelling or labelling in cavities.

Collamat® design – Electronics, drive unit, backing paper re-winder and control panel integrated in one, space-saving unit.

Modularity – The Collamat® well-known module rail design facilitates the installation of printers, scanners or other devices. Easy adaptation to new applications. Fast change-over times.

Easy operation – Settings can easily be changed by four potentiometers.


Fast set up – Set the label scanner, pre-dispensing, label position and application speed – and you are ready to work.

TECHNICAL DATA

| | |
|-------------------------|---|
| Operational speed | 1 – 50 m/min (3.3 - 164 ft/min) |
| Max. label width | 95 mm (3 3/4") or 160 mm (6 1/4") |
| Labelling accuracy | ± 1 mm (1/32") |
| Min. label length | 10 mm (3/8") |
| Max label reel diameter | 250 mm (9 7/8") or 350 mm (13 3/4") |
| Connectivity | Outputs: Signals for printer and error Inputs: Goods scanner and end of label detection |
| Settings | By potentiometers |
| Drive | 2-phase stepper motor |
| Control | Microprocessor |
| Voltage | 115 / 230 V; 60 / 50 Hz; 198 VA Feed button for manual label dispensing, i.e. threading the label web |
| Applicators | Spring loaded flap, flap with magnet, blow-on, tamp-on |
| Version | Right or left |
| Options | Side labelling kit, extended peel plate, pressure brushes, label end detection, digital control box, etc. |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® C 8600



FEATURES

Speed synchronisation – Automatic continuous adjustment to the actual line speed by encoder.

Zero down time – Two units operating in the non-stop mode guarantee you continuous production flow with minimal manpower.

User-friendly – With the intuitive menu structure the handling is safe and simple.

Memory – The capability to store 32 programs enables quick and reliable product change-over.

Precise labelling – Constant stop resolution over the whole speed range.


Monitoring – Current application data and error messages can be observed by the operator on the monitor's display or read out on a PC.

TECHNICAL DATA

| | |
|-------------------------|--|
| Operational speed | 1-50 m/min. (3.3-164 ft/min.) |
| Max. label width | 95 mm (3 3/4") or 160 mm (6 1/4") |
| Labelling accuracy | ± 1 mm (1/32") |
| Max label reel diameter | 250 mm (9 7/8") or 350 mm (13 3/4") |
| Connectivity | Outputs: Signals for printer and error Inputs: Goods scanner, encoder, end of label detection |
| Settings | By a separate control box |
| Drive | 3 phase stepper motor |
| Control | Microprocessor |
| Voltage | 115 / 230 v, 60/50 HZ, 198 VA |
| Applicators | Spring loaded flap, flap with magnet, blow-on, tamp-on, fixed |
| Version | Left / right |
| Options | Side labelling kit, extended peel plate, pressure brush/rollers/ fingers, label end detection, etc. |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® C 9100



Collamat®

FEATURES

Robust design – For stability under rough conditions.

High speed – The system is capable to follow your production up to speeds of 100 m/min.

Flexibility – Due to the modular design the system can be assembled or reconfigured into any production line also where space is a problem.

Large labels – Label rolls up to 400 mm and up to 250 mm width make restriction of size no issue.

Independent – Encoder speed adaptation and non-stop configuration offers you highest possible availability with minimal manpower.

User-friendly – With the intuitive menu structure the operating of the labeller is easiest possible.


Swiss design – Minimal wear and tear ensuring reliable and consistent labelling accuracy.

TECHNICAL DATA

| | |
|----------------------------|---|
| Dispensing speed | 100 m (328 ft) / 60 m (197 ft) / 40 m (131ft) |
| Passing width of label web | 95 mm (3/4") / 160 mm (6 1/4") / 250 mm (7") |
| Labelling accuracy | ± 1 mm (1/32") |
| Label reel | Max outer diameter 350 mm (13 3/4") |
| Drive | 3 phase-stepper motor |
| Control unit | Micro-processor control unit, SMD-technology, non stop labelling, 32 label programs, service functions, profiling, multiple labelling |
| Power supply | 110-240 V / 50-60 Hz / 480 VA |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® CP 21 - C 2600 ECO



FEATURES

Flexibility – Wide product size range thanks to the adjustable rollers.

Collamat® design – Electronics, drive unit, backing paper re-winder and control panel integrated in one, space-saving unit.

Modularity – The Collamat® famous module rail design facilitates the installation of printers, scanners or other devices. Easy adaptation to new applications. Short change-over times.

Easy operation – Settings can easily be changed by 3 potentiometers.


Fast set up – Set the label scanner, pre-dispensing and application speed – and you are ready to work.

TECHNICAL DATA

| | |
|--------------------------|--|
| Operational speed | 3 – 14 m/min (9.8 – 46 ft / min) |
| Operational width | 95 mm (3 3/4") |
| Labelling accuracy | ± 1 mm (1/32") |
| Min. label length | 10 mm (3/8") |
| Max. label reel diameter | 250 mm (9 7/8") or 350 mm (13 3/4") Min product diameter – 10 mm (3/8") Max product diameter – 120 mm (4 3/4") |
| Settings | By potentiometers |
| Drive | 2-phase stepper motor |
| Control | Microprocessor |
| Voltage | 115 / 230 V; 60 / 50 Hz; 138 VA |
| Version | Right |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® CP 21 - C 4300 ECO



FEATURES

Flexibility – Wide product size range thanks to the adjustable rollers.

Collamat® design – Electronics, drive unit, backing paper re-winder and control panel integrated in one, space-saving unit.

Modularity – The Collamat® famous module rail design facilitates the installation of printers, scanners or other devices. Easy adaptation to new applications. Fast change-over times.

Easy operation – Settings can easily be changed by 4 potentiometers.

Fast set up – Set the label scanner, pre-dispensing, label position and application speed – and you are ready to work.

TECHNICAL DATA

| | |
|--------------------------|--|
| Operational speed | 3 – 14 m/min (9.8 – 46 ft / min) |
| Operational width | 95 mm (3 3/4") |
| Labelling accuracy | ± 1 mm (1/32") |
| Min. label length | 10 mm (3/8") |
| Max. label reel diameter | 250 mm (9 7/8") or 350 mm (13 3/4") Min product diameter – 10 mm (3/8") Max product diameter – 120 mm (4 3/4") |
| Connectivity | Outputs: Signals for printer and error Inputs: Goods scanner and end of label detection |
| Settings | By potentiometers |
| Drive | 2-phase stepper motor |
| Control | Microprocessor |
| Voltage | 115 / 230 V; 60 / 50 Hz; 138 VA |
| Feed button | For manual label dispensing, i.e. threading the label web |
| Version | Right |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® Etiprint Inkjet



Collamat®

FEATURES


- HP based technology, optimized for use with Collamat® S 50 or Collamat® S 100.
- Build print jobs using MicroDraw PC software.
- The PC-based Microdraw software eases building of print jobs.
- Transfer job via USB stick or Minitouch display.
- Add, edit or remove print objects.
- Rotate & scale text, graphics, numbers.
- Set print resolution in software.
- Small size makes integration into existing Collamats easy.
- Place a cartridge in the head and start printing.
- Speed synchronisation with the Collamat® without encoder.

TECHNICAL DATA

| | |
|--------------------|---|
| Max printing speed | 150m/min at 150 x 150 dpi |
| Technology | HPTIJ 2 |
| Print heads | 1 pen integrated (dep on model) |
| Print height | Max. 12.7 mm (1/2") |
| Design software | MicroDraw (for winPC) |
| Memory | 1 print job in uni (dep. On model) |
| Print features | Max. Length 2400 px (-10 cm (4") 600 dpi), unicode support in text and objects, rotation of static objects, works with mm/ inch/point/pixel |
| Signals | Low ink signal (diode), Print signal (diode), Built-in sensor |

All data are indicative and may be subject to alteration

Collamat® Etiprint Print & Apply



FEATURES

Flexible printing – Each label can be printed on demand with variable data.

Open frame design – Designed to integrate OEM print engines.

Flexibility – Can be used for side, top, bottom, and over edge applications.

Compact design – Made for industrial environments and easy integration.

Swiss quality – Highly durable mechanics suitable for rugged conditions.

Increasing product information – Create barcodes and graphics on your labels.

Adaptability – Different applicators available for various tasks.


Communication – Printing directly from PC, network or from internal memory.

TECHNICAL DATA

| | |
|----------------------------|---|
| Label reel size core / ext | 40 mm / 300 mm (1 1/2" / 11 7/8") |
| Min. label width | 25 mm (1") |
| Min. label length | 30 mm (1 1/8") |
| Max label length | 150 mm (5 7/8") |
| Labels per minute (max) | 80 (depending on printer) |
| Printer technology | Thermal direct / thermal transfer technology |
| Printer data | Depending on the fitted model |
| Control system | Parameter settings over interactive display |
| Dimensions | 447 x 449 x 725 mm (17 5/8" x 17 3/4" x 28 1/2") (length x depth x height) |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® Etiprint Inline 30



FEATURES

Efficiency – Optimal use of the printer's performance combined with the well known Collamat® traction unit.

Technology – Best print quality due to slow printing speed at the fast application speed.

Performance – Output of up to 150 labels per minute.

Speed synchronisation – Application speed follows automatically the production performance (with option encoder).

Energy saving – No expensive compressed air needed because of applying labels with wipe on technology.

Accuracy and reliability – Built with approved Collamat® parts.

Flexible adapter program – All adapters from the Collamat® program available.

TECHNICAL DATA

| | |
|-----------------------|--|
| Max application speed | 30 m/min (98 ft/min.) |
| Application accuracy | ± 1 mm (1/32") |
| Printer | Ready for OEM print engines Sato, Cab, Zebra (others on request) |
| Print width | 4", 6" |
| Drive unit | Stepper motor based on Collamat® 6600 |
| Unwinder diameter | 350 mm (13 3/4") |
| Label scanner | Optical or mechanical |
| Speed synchronisation | Potentiometer regulation |
| Power supply | 220V AC |
| Communication | On request |
| Options | Encoder, side labeling kit, label low sensor, signal lamp |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat® Etiprint Inline 50



Collamat®

FEATURES

Efficiency – Optimal use of the printer's performance combined with the well known Collamat® traction unit.

Technology – Best print quality due to slow printing speed at the fast application speed.

Performance – Output of up to 150 labels per minute.

Speed synchronisation – Application speed follows automatically the production performance (with option encoder).

Energy saving – No expensive compressed air needed because of applying labels with wipe on technology.

Accuracy and reliability – Built with approved Collamat® parts.

Open frame design – Designed to integrate several OEM print engines.

TECHNICAL DATA

| | |
|-----------------------|--|
| Max application speed | 50 m/min (164 ft/min) |
| Application accuracy | ± 0,1 mm (1/32") |
| Printer | Ready for OEM print engines Sato, Cab, Zebra (others on request) |
| Print width | 4", 6" |
| Drive unit | Stepper motor based on Collamat® C 8600 |
| Unwinder diameter | 350 mm (13 3/4") |
| Label scanner | Optical or mechanical |
| Speed synchronisation | Measured with encoder |
| Power supply | 220V AC |
| Communication | On request |
| Options | Encoder, side labeling kit, label low sensor, signal lamp |
| Approbation | CE/Gost |

All data are indicative and may be subject to alteration

Collamat® Etiprint Pallet labeller



Collamat®

FEATURES

Front- and side labelling.

Correct placement of A5/SSCC labels in compliance with GS1 Norm.

Flexible printing – designed to integrate OEM printing modules.

Swiss quality – highly durable mechanics suitable for tough conditions.

TECHNICAL DATA

| | |
|---------------|--|
| Labels | Paper labels on rolls D=300mm (11 7/8"), d=76mm (3") |
| Printers | Zebra®Pax, Sato® - other types on request |
| Output | 2 pallets per minute |
| Communication | PLC lines |
| Activation | Via design software with customer ERP interface |
| Control | Siemens® Micro Panel |
| Placement | 1 stop handling for automatic application of the two identical labels |
| Accessories | Supplied with extensive machine documentation and training documentation |
| Options | Barcode readability check, Profibus activation, remote maintenance, 3-page labelling |
| Approbation | CE |

All data are indicative and may be subject to alteration

Collamat®

Hofackerstrasse 73, CH-4132 Muttenz, Switzerland
Tel.: +41 61 756 28 28, Fax: +41 61 756 29 29
contact@collamat.ch, www.collamat.ch